

Application No. 10/764404
Reply to Office action of 6/23/2005
Page 2

Amendments to the claims:

This listing of claims will replace all prior versions and listing of claims in the application.

Claims 7 and 8 are amended.

Claim 6 is canceled.

Listing of Claims:

1. (Original) A limiting circuit comprising:
an excess signal circuit for inputting an input signal and a limitation signal, and comparing them with each other so as to output an excess amount thereof as an excess signal when the input signal exceeds the limitation signal; and
a signal output circuit for inputting the input signal and the excess signal, subtracting the excess signal from the input signal of which subtracted amount is output as an output signal.
2. (Original) The limiting circuit according to claim 1, further comprising a limitation signal circuit having such a structure that a constant current source and a resistor are connected in series and a voltage on a serial node is fetched as the limitation signal through a buffer.
3. (Original) The limiting circuit according to claim 2, wherein the excess signal circuit has such a structure that a transistor to which the input signal is supplied as a control signal and a resistor are connected in series, a first current corresponding to the input signal flows, a voltage on a node of the transistor and the resistor is set to be a comparison voltage, and a second current corresponding to an excess flows when the comparison voltage exceeds an output voltage of the buffer, and
the signal output circuit outputs, as the output signal, a third current corresponding to a difference between the first current and the second current.

Application No. 10/764404
Reply to Office action of 6/23/2005
Page 3

4. (Original) The limiting circuit according to claim 1, further comprising a limitation signal circuit having such a structure that a constant current source and a resistor are connected in series and a voltage on a serial node is fetched as the limitation signal.

5. (Original) The limiting circuit according to claim 4, wherein the excess signal circuit has such a structure that a transistor to which the input signal is supplied as a control signal and a resistor are connected in series, a first current corresponding to the input signal flows, a voltage on a node of the transistor and the resistor is set to be a comparison voltage and is differentially amplified with the limitation signal, and a second current corresponding to an excess flows when the comparison voltage exceeds the limitation signal, and

the signal output circuit outputs, as the output signal, a third current corresponding to a difference between the first current and the second current.

6. (Canceled)

7. (Currently Amended) ~~An [[The]] electric motor driving device according to claim 6, comprising:~~

an error amplifier for generating an error output signal depending on a difference between a reference signal and a current detection signal corresponding to a current flowing to an electric motor;

a limiting circuit for inputting the error output signal, limiting a value to be a predetermined value, and outputting a limitation error output signal; and

a driving circuit for PWM driving the electric motor based on the limitation error output signal and a signal corresponding to a sine wave-shaped rotating position signal of the electric motor,

wherein the driving circuit has a multiplier for multiplying the limitation error output signal by the sine wave-shaped rotating position signal of the electric motor and outputting a PWM command signal, a PWM converting block for forming a PWM

Application No. 10/764404
Reply to Office action of 6/23/2005
Page 4

control signal based on the PWM command signal, and a driving stage block for outputting an electric motor driving current based on the PWM control signal.

8. (Currently Amended) An [[The]] electric motor driving device according to claim 6, comprising:

an error amplifier for generating an error output signal depending on a difference between a reference signal and a current detection signal corresponding to a current flowing to an electric motor;

a limiting circuit for inputting the error output signal, limiting a value to be a predetermined value, and outputting a limitation error output signal; and

a driving circuit for PWM driving the electric motor based on the limitation error output signal and a signal corresponding to a sine wave-shaped rotating position signal of the electric motor,

wherein the limiting circuit according to claim 6 comprises:

an excess signal circuit for inputting an input signal and a limitation signal, and comparing them with each other so as to output an excess amount thereof as an excess signal when the input signal exceeds the limitation signal; and

a signal output circuit for inputting the input signal and the excess signal, subtracting the excess signal from the input signal of which subtracted amount is output as an output signal.